



Officina Meccanica Rivoltana Srl

CLIENTE / CUSTOMER : BASSI LUIGI & C. SPA

RIVESTIMENTO ESTERNO : IN ACCORDO ALLA NORMA DIN 30670 CON FUSION BONDED EPOXY TIPO SCOTCHKOTE 206N 3M + ADESIVO POLIETILENE TIPO FLAMULIT HTC 222 DUPONT + POLIETILENE TIPO FLAMULIT HTC 214 SPESSORE TOTALE DEL RIVESTIMENTO 2,0 MM.
RIVESTIMENTO INTERNO : CON FUSION BONDED EPOXY TIPO SCOTCHKOTE 206 N 3M

EXTERNAL COATING : IN ACCORDANCE DIN 30670 WITH FUSION BONDED EPOXY TYPE SCOTCHKOTE 206N XLG 3M + ADHESIVE POLYETHYLENE TYPE FLAMULIT HTC 222 DUPONT + POLYETHYLENE TIPO FLAMULIT HTC 214 TOTAL THICKNESS 2,0 MM.
INTERNAL COATING : WITH FUSION BONDED EPOXY TYPE SCOTCHKOTE 206N XLG 3M



Strada Rivoltana snc
24040 Arzago d'Adda (Bg) ITALY
V.A.T. IT02308570163

<http://www.omrcoat.com/> e-mail: omrcoat@tin.it

Tel. + 00 39 (0) 363 879955



Fax. + 00 39 (0) 363 87655